


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H01Q 1/12	A1	(11) International Publication Number: WO 99/22418 (43) International Publication Date: 6 May 1999 (06.05.99)
(21) International Application Number: PCT/GB98/01220 (22) International Filing Date: 27 April 1998 (27.04.98) (30) Priority Data: 9722450.5 23 October 1997 (23.10.97) GB (71)(72) Applicants and Inventors: JESMAN, Andrew [GB/GB]; Highdown, Longdown Road, Guildford, Surrey GU4 8PP (GB). JESMAN, Christopher [GB/GB]; Westhaven, 6 Rose- briars, Esher Park Avenue, Esher, Surrey KT10 9NN (GB). (74) Agent: GEE & CO.; Chancery House, Chancery Lane, London WC2A 1QU (GB).		(81) Designated States: AU, CA, NO, NZ, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: MATCHING DEVICE FOR A MULTI-FREQUENCY ANTENNA (57) Abstract <p>An antenna coupling unit (1) for use with a dual-frequency glass-mount antenna (3) incorporates additional circuitry in the form of suitably shaped patterns of conductive cladding material (10, 11 and 13 to 20) to provide resonance at both antenna frequencies.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

Matching device for a multi-frequency antenna

The present invention relates to a matching device for a screen mounted multi-frequency antenna, particularly, although not exclusively for use with a cellular telephone.

In our earlier U.K. Patent Application No. 9700859.3 we described a dual-frequency antenna for use with PCN (E-Net) and GSM (D-Net) cellular telephony networks. Such an antenna which utilised a phasing coil to separate two individual radiating elements could be used with a conventional vehicle body mount. However, such an antenna could not be used effectively on a glass mount base with a conventional matching device.

Matching devices for use with glass mount bases and which provide the necessary compatibility between an antenna and a telephone within a vehicle are known. In particular, European Patent No. 0 456 350 which is in the name of the present Applicants, describes just such a matching device or coupling unit for use with a screen mounted antenna. The unit includes a circuit board substrate of suitable dielectric material having patterns of conductive cladding material on both surfaces thereof to provide the requisite matching and balancing functions. However, the unit is suitable for use with a single frequency antenna.

It is therefore an object of the present invention to provide a glass mount coupling unit suitable for use with a multi-frequency antenna and a cellular telephony antenna in particular.

According to the present invention there is provided a glass mount antenna coupling unit of the type above described for use with an antenna operating at more than

- 2 -

one frequency, characterised in that in addition to providing a capacitive coupling to a base mounting of the antenna, the conducting material is so shaped and arranged to form a circuit, including high-pass and low-pass filters, which is resonant at each said frequency.

The coupling unit is intended to provide the maximum power transfer at the frequencies of interest. Thus the circuit may contain one or more of the following circuit elements. Firstly, passive printed circuit filters relying on a combination of inductive and capacitive tracks to produce frequency selective circuits. Secondly, strip line resonators formed of stepped impedance, direct and parallel coupled resonators, stub loaded configurations and grounded stubs (direct coupled) structures.

In order to aid in understanding the invention a specific embodiment thereof will now be described by way of example and with reference to the accompanying drawings, in which:

Figure 1 is a sectional side view of a coupling unit in accordance with the invention;

Figure 2 is a view of the circuit board of Figure 1, from the screen side of the board;

Figure 3 is a view of the opposite side of the circuit board;

Figure 4 is a superimposed view of both sides of the circuit board from the screen side; and

Figure 5 is an equivalent circuit diagram of the coupling unit shown in the above figures;

Figure 6 is a sectional side view of the separate components of a multi-frequency antenna for use with the coupling unit of Figures 1 to 5;

Figure 7 is a cross-sectional side view of the antenna of Figure 6 at an intermediate stage of assembly;

- 3 -

Figure 8 is a similar view to that of Figure 7 at later stage of assembly;

Figure 9 is a similar view a still further stage of assembly;

Figure 10 is side view of the assembled antenna of Figure 6 with a panel mount base; and

Figure 11 is an exploded view of a glass-mount base for the antenna of Figure 6.

Referring to the Figures 1 to 5, a coupling unit 1 in accordance with the invention comprises a circuit board substrate 2 of any suitable insulating material, provided on both sides with conductive cladding elements. These elements are so configured to define a set of capacitive, inductive and resistive elements which cause the unit to resonate at both GSM and PCN frequencies whilst providing capacitive coupling to the base of a dual frequency antenna 3.

Referring to Figure 1, the unit 1 is mounted on a suitable dielectric such as a glass screen 4 of a vehicle (not shown) with a first side 5 of the substrate 2 adhesively secured thereto. The substrate 2 is positioned within a conductive housing 6 which incorporates an aperture 7 for receiving a coaxial cable 8 to be coupled to the unit 1. The cable 8 is soldered or otherwise physically secured to the substrate 2 on its opposite or second side 9. The dual frequency antenna 3 is adhesively secured on the opposite side of the screen 4 in a facing relationship to the first side 5 of the substrate 2.

Clearly, the precise arrangement of the cladding elements making up the coupling and resonant circuitry depends on the material used for the substrate 2 and the frequencies at which resonance should occur. It will be therefore understood that various alterations and

- 4 -

modifications may be made to the arrangement as illustrated without departing from the scope of the invention.

Consequently, the circuitry may be best understood by reference to the equivalent circuit diagram of Figure 5, and be referencing the various capacitive and inductive elements to corresponding physical elements, including the cladding, shown in Figures 1 to 4:

- L1,L2 - inductance formed by tracks 10,11 on the substrate 2.
- L3 - inductance formed by the feed 20 from the inner conductor of the coaxial cable 12.
- L4,L6 - inductance formed by overlapping elements 13 and 14 on opposite sides of the substrate.
- L5 - further inductance formed by overlapping elements 13 and 14.
- C1 - capacitance formed by overlapping elements 13 and 14.
- C2 - capacitance formed by overlapping elements 15 and 14.
- C3 - capacitance formed by overlapping elements 16 and 14.
- C4 - further capacitance formed by overlapping elements 15 and 14.
- C5 - capacitance formed by overlapping elements 17 and 14.
- C6,C7 - capacitance formed by elements 18,19 bordering element 14.
- C8 - distributed capacitance formed by the metallic enclosure 6.
- C9 - capacitance formed across the screen 4 of the vehicle.

- 5 -

It is to be understood from the above that the fields from all the conducting elements contribute to provide the matching mechanism to the antenna. Thus it will be noted from the equivalent circuit that some of the cladding elements react to form different reactive values in different parts of the circuit.

Further points to be noted from the above are that the inductance of the feed point can be minimised, where necessary by introducing an un-grounded relief hole 21 in the substrate 2 which creates counter-capacitance. Furthermore, although the gap 22 between elements 13 and 15 is shown as being tapered a constant width gap has been found to perform adequately in practice. Additionally, by changing the length of the element 19 the resonance of the circuit may be altered.

Referring to the Figures 6 to 10, the antenna 101 comprises a combined bottom crimp terminal and first radiating element 102, a metallic helically wound spring or phasing coil 103, a top crimp terminal 104, and a stainless steel rod or second radiating element 105. The bottom crimp terminal 102 is formed with an end connector suitably threaded or otherwise formed for connection to a base 107 mounted on the roof 108 or other body panel of a vehicle. Antenna signals are fed to terminals (not shown) within the base 107 which terminals connect to a coaxial or other suitable antenna lead 106.

The antenna is assembled in a series of stages as set out in Figures 7 to 9 of the drawings. Firstly, one free end 109 of the coil 103 is crimped to a crimp point 110 in the bottom crimp terminal and first radiating element 102. The other free end 101 of the coil 103 is then crimped within the top crimp terminal 104 leaving space within the terminal 104 for the second radiating element 105 to be

- 6 -

similarly inserted and crimped in place. To complete the basic assembly, a pressed butterfly 112 is secured to the remaining free end 113 of the element 105 to facilitate plastics material encapsulation.

Turning to Figures 8 and 9, these show a two step moulding process, in which firstly (Figure 8) a black engineering plastics material moulding 114 is formed around the coil 103. A second later moulding stage follows (Figure 9), in which a black plastics material moulding 115 is formed around the bottom crimp terminal 102 and the previously encapsulated coil 103,114. Such a two stage process enhances the surface finish of the completed moulding which otherwise might reveal the contours of the encapsulated coil. A separate end plastics material end tip 116 is moulded around the butterfly 112 at the free end of the element 105.

An assembled antenna is shown in Figure 10 attached to the base 107 of the panel mount type on the vehicle containing the cellular and/or GPS equipment. In a variant intended for use with the coupling unit 1, the antenna (not shown) is secured by a threaded connection to a glass-mount base 207, as shown in more detail in Figure 11. As is clear from Figure 11, no circuitry is required in the base 207 to provide the capacitive link to the coupling unit 1 as the bracket 208 provides the necessary capacitance.

It will be appreciated by one skilled in the art that the above antenna could, instead of being made up of several separate elements, be formed as a unitary item which would advantageously increase the performance and simplify assembly of the antenna. However, the skilled person would also recognise the difficulty in manufacturing such an antenna and in particular the difficulty of

- 7 -



ensuring that the first and second radiating elements remain coaxial with the phase coil.

Finally, it should be noted that any reference to a glass in the above description should be taken to refer equally to a composite or plastics material body panel which exhibits dielectric properties.

- 8 -

Claims:

1. An antenna coupling unit for capacitively coupling to a multi-frequency antenna mounted on a dielectric such as windscreen, the unit including a substrate of suitable dielectric material having patterns of conductive cladding material on both surfaces thereof to provide antenna matching and balancing and wherein the conducting material is further shaped and arranged to form a circuit, including high-pass and low-pass filters, which circuit is resonant at a plurality of antenna operating frequencies.
2. A coupling unit as claimed in Claim 1, wherein the circuit is resonant at both GSM and PCN frequencies.
3. A coupling unit as claimed in Claim 1 or Claim 2, wherein the conducting material includes a set of inductive and capacitive tracks.
4. A coupling unit as claimed in any preceding Claim, wherein the conducting material includes a set of strip line resonators.
5. A coupling unit as claimed in any preceding Claim, wherein the substrate includes an un-grounded relief hole.
6. A coupling unit substantially as described herein with reference to Figures 1 to 4 and Figure 5 of the accompanying drawings.



2/7




FIG. 3

3/7




FIG. 4

4/7




FIG. 5

5/7









FIG. 10



7/7

FIG. 11



INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/01220

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H01Q1/12

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H01Q H01P

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 297 08 536 U (JESMAN ANDREW ;JESMAN CHRISTOPHER (GB)) 24 July 1997 see page 7, line 10-23; figure 4	1-5
X	US 5 278 572 A (HARADA TAKUJI ET AL) 11 January 1994 see the whole document	1-3
X	US 5 557 290 A (WATANABE HIRONOBU) 17 September 1996 see column 6, line 27 - column 9, line 65; figure 10	1-3
Y	DE 93 09 897 U (MAY HANS GEORG) 23 September 1993 see page 4, line 9 - page 6, line 3; figures 6,7	1-3
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

Date of the actual completion of the international search

6 August 1998

Date of mailing of the international search report

14/08/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Van Dooren, G

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/01220

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 992 800 A (PARFITT DALE R) 12 February 1991 see the whole document ----	1-3
A	EP 0 456 350 A (PANORAMA ANTENNAS LTD) 13 November 1991 cited in the application see figures 1-4 ----	1-5
A	EP 0 376 643 A (HARADA IND CO LTD) 4 July 1990 see column 2, line 45 - column 4, line 17; figures 1-3 ----	1,4
A	US 5 283 589 A (BLEVINS PETER D) 1 February 1994 see figures 3,4 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. l. Application No

PCT/GB 98/01220

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 29708536 U	24-07-1997	NONE	
US 5278572 A	11-01-1994	JP 2515624 B JP 4170102 A	10-07-1996 17-06-1992
US 5557290 A	17-09-1996	JP 2509457 B JP 6260815 A	19-06-1996 16-09-1994
DE 9309897 U	23-09-1993	NONE	
US 4992800 A	12-02-1991	NONE	
EP 0456350 A	13-11-1991	AU 645084 B CA 2078977 A AU 7739391 A DE 69115753 D DE 69115753 T ES 2081432 T GB 2245430 A,B US 5212492 A DK 456350 T	06-01-1994 24-03-1994 03-12-1992 08-02-1996 15-05-1996 01-03-1996 02-01-1992 18-05-1993 11-03-1996
EP 0376643 A	04-07-1990	JP 2117879 C JP 2174404 A JP 8021812 B AU 598980 A DE 68913180 D DE 68913180 T ES 2051376 T US 5291210 A	06-12-1996 05-07-1990 04-03-1996 05-07-1990 24-03-1994 26-05-1994 16-06-1994 01-03-1994
US 5283589 A	01-02-1994	NONE	